

DATASHEET

# Taubmans TAUBMANS EASYCOAT PREP SEALER & UNDERCOAT

# TAUBMANS

Product Code:  
199500



## TAUBMANS EASYCOAT PREP SEALER & UNDERCOAT

The Taubmans® EASYCOAT® interior range has been designed with a family home in mind. With Microban® technology, EASYCOAT protects against the growth of bacteria, mould and fungus, making it ideal for damp and humid areas like the kitchen, bathroom and laundry.

EASYCOAT is also low in VOCs, which means it has minimal impact on the indoor air quality, and it is low in odour. Add the approval from Sensitive Choice® for asthma and allergy friendly products, and it's easy to see why EASYCOAT is the safe family choice.

## USES

Working with new, unpainted or coloured areas?

Start with EASYCOAT Prep. EASYCOAT prep is a sealer and undercoat in one, and this makes it easier to paint over new or existing paint as it allows for good adhesion and blocks out dark and existing colours. It also provides a smoother and more professional looking topcoat.

## FEATURES AND BENEFITS

<b>ASTHMA &amp; ALLERGY FRIENDLY</b>	Approved by the National Asthma Council Australia's Sensitive Choice® program. Products approved by the Sensitive Choice Program may help people with asthma and allergies
<b>MOULD RESISTANT</b>	Helps prevent the growth of mould, mildew and fungus in damp areas
<b>HIGH OPACITY</b>	Excellent hiding properties.
<b>EASY TO APPLY</b>	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>AUSTRALIAN STANDARD</b>	AS2311, AS3730.23
<b>ACRYLIC BINDER</b>	Superior adhesion, flexibility, gloss retention & durability
<b>WATER BASED FORMULA</b>	Easy clean up with water

## DATASHEET

<b>MICROBAN</b>	EASYCOAT with Microban® technology helps to protect painted surfaces from the growth of bacteria, mould and fungus. These built-in antimicrobial properties make EASYCOAT ideal for walls and ceilings in bedrooms, kitchens and bathrooms, as well as damp, high humidity areas. Microban technology is limited to the treated surface and is not designed to protect users or others from disease-causing microorganisms. Microban is not a substitute for normal cleaning practices.
-----------------	---

<b>LOW VOC PRODUCT</b>	VOC <5g/L
------------------------	-----------

## PRODUCT SPECIFICATIONS

<b>VOC LEVELS</b>	<5g/Litre
<b>FLAT</b>	Designed to produce flat uniform finish with no roller marks
<b>GLOSS LEVEL</b>	0-5%
<b>DRY TIMES: TOUCH DRY</b>	30 mins
<b>DRY TIMES: RECOAT</b>	2 hours
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>
<b>WHITE BASE</b>	Tint your desired colour from a White base
<b>SIZES AVAILABLE</b>	500ml 1L 2L 4L 10L 15L

## SURFACE PREPARATION

<b>PREPARATION</b>	<p>Surfaces must be clean, dry and free from all surface contamination. Treat mould with Flood® Mould Action or bleach then rinse with fresh water. Fill in the surface defects with suitable filler, putty or sealant. Avoid using masking tape on walls and ceiling paints. For wallpaper, make sure all glue residue is sanded and washed off from the surface before applying one coat of an oil based undercoat such as Taubmans Tradex Quick Dry Oil Based Undercoat.</p> <p>NEW WORK: Timber – Sand smooth and apply EASYCOAT Prep. Tannin rich timbers should be primed with Taubmans 3 in 1 Prep. Cement Render &amp; Concrete – New concrete and cement render must be allowed to cure for 28 days before painting. Plasterboard &amp; Fibre Cement – Dust down the surface and apply one coat of EASYCOAT Prep. Not suitable for set plaster.</p> <p>PREVIOUSLY PAINTED: Remove all loose and flaking paint by scraping or sanding previously painted areas until smooth. Spot prime any area that is now bare by following the "new work" directions above. Old Enamels, Varnishes &amp; Stains – Thoroughly sand the surface and clean with a mild detergent solution. Rinse with clean water and apply one coat of EASYCOAT Prep.</p>
<b>TEMPERATURE MAX</b>	35 (°C)
<b>TEMPERATURE MIN</b>	10 (°C)
<b>CARE AFTER PAINTING</b>	Avoid exposure to steam for 48 hours.

DATASHEET

## APPLICATION

<b>WET FILM THICKNESS</b>	80 -85 microns
<b>DRY FILM THICKNESS</b>	25 - 30 microns
<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
<b>BRUSH, ROLLER, SPRAY</b>	Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
<b>NAP ROLLER</b>	12mm - 14mm Pile Roller
<b>CURING</b>	Avoid exposure to steam and condensation for 48 hours after painting.
<b>COVERAGE</b>	Up to 12 m <sup>2</sup> /litre
<b>COATS REQUIRED</b>	One

## PRECAUTIONS

<b>GENERAL SAFETY INFORMATION</b>	<p>WALL PAINTS</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p> <p>CEILING</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
<b>FIRST AID INFORMATION</b>	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a></p>
<b>ENVIRONMENT INFORMATION</b>	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a>

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact

**DATASHEET**

Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

**CUSTOMER SERVICE/COMPANY CONTACT**

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)