

## DATASHEET

# Taubmans Armawall Ultrasand

# TAUBMANS

Product Code:  
310316


## Taubmans Armawall Ultrasand

Taubmans Armawall Ultrasand is a durable, exterior matt finish, which gives a medium profile cement rendered appearance. It can be left as a matt finish, or can be over coated with Armawall Armashield or Armawall Satin for extra durability and substrate protection.

## USES

Brick, fibro, cement render, AAC panels and blocks and other masonry surfaces. DO NOT use on timber surfaces.

## FEATURES AND BENEFITS

<b>LOW VOC</b>	Contains low level of VOC to conform to requirements of Green Building Council of Australia (GBCA).
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>ACRYLIC BINDER</b>	Superior adhesion, flexibility, gloss retention & durability
<b>WATER BASED FORMULA</b>	Easy clean up with water

## PRODUCT SPECIFICATIONS

<b>COLOUR RANGE</b>	Available in a wide range of colours
<b>PROFILE</b>	Medium texture profile - Contemporary render-like finish
<b>SPREAD RATE</b>	Spread rate – Up to 8m <sup>2</sup> /litre
<b>CLEAN UP</b>	Water, away from drains and watercourses.
<b>VOC LEVELS</b>	< 50g/Litre
<b>DRY TIMES: TOUCH DRY</b>	60 mins

## DATASHEET

<b>DRY TIMES: RECOAT</b>	4 hours (Note: This may be lengthened in damp, cold or humid conditions. Do not apply at temperatures below 10°C.)
<b>15L AVAILABLE SIZES</b>	15l
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>
<b>WHITE BASE</b>	Tint your desired colour from a White base

## SURFACE PREPARATION

<b>NEW/BAREWORK</b>	New cement render, masonry and concrete surfaces should be allowed to cure for 28 days. Off form concrete should be thoroughly cleaned by acid etching, water or sand blasting to ensure all bond breaker oils are removed. Armawall Ultrasand may be applied over porous or absorbent masonry surfaces such as brick and render without a primer. If in doubt apply Armawall Primer thinned 25-50% with water, or apply a test area. Seal tilt slab concrete and CFC with Armawall Sealer/ Bonder thinned 50% with i coat LO- 2 Thinner to ensure adhesion of topcoats.
<b>SUBSTRATE MOISTURE CONTENT</b>	Moisture content of the substrate must be no greater than 15% wood-moisture-equivalent (WME) prior to or during application, to ensure optimal coating system performance
<b>TEMPERATURE MIN</b>	10 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>RECOATTEMPDEGREES</b>	25 (°C)
<b>RECOATHUMIDITYPERCENTAGE</b>	50 (%)

## APPLICATION

<b>ODOUR</b>	Low
<b>APPLICATION</b>	Apply 2 coats of Armawall Ultrasand using a long nap roller.
<b>WET FILM THICKNESS</b>	120 - 125 microns
<b>DRY FILM THICKNESS</b>	60 - 65 microns
<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
<b>COARSE TEXTURE ROLLER</b>	Yes
<b>NAP ROLLER</b>	Low Profile 16mm Pile Roller
<b>COVERAGE</b>	Up to 8m <sup>2</sup> /litre
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS</b>	10
<b>APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS</b>	35

## DATASHEET

### COATS REQUIRED

Two

## PRECAUTIONS

### GENERAL SAFETY INFORMATION

#### WALL PAINTS

#### SAFETY

Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

#### CEILING

#### SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

### FIRST AID INFORMATION

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686  
Further information: [www.taubmans.com.au](http://www.taubmans.com.au)

### ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit [paintback.com.au](http://paintback.com.au)

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)