

DATASHEET

Taubmans Armawall Pearl

TAUBMANS

Product Code:
305014


Taubmans Armawall Pearl

Armawall Pearl top coat is a third step in the Armawall Texture Coating System with top coats that are designed to give excellent dirt shedding properties, substrate protection, and greater flexibility. Armawall Pearl contains fine and coarse aggregates which gives a coarse grainy texture that can bridge hairline cracks. This premium, high build texture coating finish can be rolled on to give a bold textured finish or be laid off with a plastic triangle to give a "plateau" flattened finish. Pearl can be left as a matt finish or over coated with Armawall Armashield or Armawall Satin for extra durability and substrate protection, or if a low sheen is preferred.

USES

Exterior cement render, masonry, fibrous cement sheeting, AAC panels and blocks, bricks and blockwork.

FEATURES AND BENEFITS

SCRUB RESISTANT	Provides a tough and durable abrasion-resistant coating
ADVANCED WASHABILITY	Resists burnishing – the formation of shinny patches on washing.
LOW VOC	Contains low level of VOC to conform to requirements of Green Building Council of Australia (GBCA).
MOULD RESISTANT	Prevents the growth of mould, mildew and fungus in damp areas
EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
ALL WEATHER PROTECTION	Built with advanced UV protection technology to resists cracking & peeling from harsh weather conditions longer
FLEXIBLE	Withstands normal substrate movements
SEAMLESS MEMBRANE	A highly flexible acrylic seamless membrane with outstanding weather and moisture resistance
VAPOR PERMEABILITY	Allows substrate to breathe to reduce moisture entrapment
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.

DATASHEET

TINTABLE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
ACRYLIC BINDER	Superior adhesion, flexibility, gloss retention & durability
MOULD PROTECTION (JOHNSTONE'S ONLY)	Encapsulated biocide which is released slowly. Slow release means the coating resists mould growth for up to 2 times longer versus conventional woodcare products
WATER BASED FORMULA	Easy clean up with water

PRODUCT SPECIFICATIONS

VOC LEVELS	< 50g/Litre
DRY TIMES: TOUCH DRY	2 hours
DRY TIMES: RECOAT	6 hours
15L AVAILABLE SIZES	15L
SDS	SDS available from the Taubmans Website taubmans.com.au
EXTENSIVE COLOUR RANGE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
WHITE BASE	Tint your desired colour from a White base

SURFACE PREPARATION

GENERAL EXTERIOR	Can include exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel
NEW WORK	<p>TIMBER</p> <p>Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar should be primed with Taubmans 3 in 1 Prep or a suitable Taubmans oil based wood primer.</p> <p>GALVANISED IRON</p> <p>Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with 240 grade paper to remove chemical treatments and allow full adhesion.</p> <p>CEMENT RENDER / MASONRY</p> <p>Allow masonry, cement render and mortar to cure for 28 days before painting.</p> <p>STEEL</p> <p>Remove rust and prime with a suitable Taubmans iron & steel primer or White Knight Rust Guard® Metal Primer.</p> <p>ZINCALUME® STEEL</p> <p>Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.</p>
PREVIOUSLY PAINTED	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)

DATASHEET

RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)

APPLICATION

WET FILM THICKNESS	1-3 mm
DRY FILM THICKNESS	1-2 mm
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
COARSE TEXTURE ROLLER PLASTIC TRIANGLE	COARSE TEXTURE ROLLER PLASTIC TRIANGLE
NAP ROLLER	Spaghetti Roller
COVERAGE	0.7 m ² /litre
MAINTENANCE - DECKING	No
APPLICATION TEMPERATURE MINIMUM DEGREES CELSIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELSIUS	35
COATS REQUIRED	One or two

PRECAUTIONS

GENERAL SAFETY INFORMATION	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use
FIRST AID INFORMATION	<p>IF SWALLOWED</p> <p>Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT</p> <p>Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT</p> <p>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION</p> <p>Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA</p> <p>24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au</p>
ENVIRONMENT INFORMATION	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DATASHEET

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au