

DATASHEET

Taubmans
Plaster Sealer

TAUBMANS

Product Code:
111532**Taubmans Plaster Sealer**

Taubmans Plaster Sealer is an oil-based prep coat that seals unpainted surfaces such as bare set plaster and brickwork, preparing them for topcoats. The foundation for a superior finish.

USES

Ideal for set plaster, brickwork, and cement render. For interior paper-faced plasterboard/gyprock etc., use Taubmans 3 in 1.

FEATURES AND BENEFITS**AUSTRALIAN MADE**

Our Aussie Heritage: Since our creation over a century ago in 1897 by George Henry Taubman, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success with our state-of-the-art plant in Clayton, VIC.

PENETRATIVE FORMULA

Low viscosity and excellent wetting properties allow the coating to penetrate the surface.

EASY TO APPLY

Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.

AUSTRALIAN STANDARD

AS2311, AS3730.22

APAS APPROVED

APAS 0171

PRODUCT SPECIFICATIONS**4L AVAILABLE SIZES**

4L

10L AVAILABLE SIZES

10L

DRY TIMES: TOUCH DRY

4 hours

DRY TIMES: RECOAT

16 hours

SDS

SDS available at www.ppgmsds.com.au

DATASHEET

SURFACE PREPARATION

TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)
NEW/BAREWORK	All surfaces must be clean and dry with all defects sanded smooth.

APPLICATION

WET FILM THICKNESS	60 - 65 microns
DRY FILM THICKNESS	25 - 30 microns
COVERAGE	Up to 16 m2/litre
COATS REQUIRED	One
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
BRUSH, ROLLER, SPRAY	Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.

PRECAUTIONS

DANGER FLAMMABLE LIQUID AND VAPOUR	<p>Warning. Flammable hydrocarbon liquid. Keep out of reach of children. Keep lid on when not in use.</p> <p>Wear solvent resistant gloves and eye protection when using. Ensure adequate ventilation and do not breathe vapour.</p>
GENERAL SAFETY INFORMATION	<p>WALL PAINTS</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p> <p>CEILING</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
FIRST AID INFORMATION	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686</p>

DATASHEET

Further information: www.taubmans.com.au

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au