

DATASHEET

# Taubmans All Weather® Exterior Low Sheen (187200, 187204, 187205)

# TAUBMANS

Product Code:  
187200



## Taubmans All Weather® Exterior Low Sheen (187200, 187204, 187205)

Taubmans All Weather Exterior Low Sheen offers superior performance against leading competitors, making it the perfect choice for exterior surfaces. Engineered with Nanoguard® Advanced Technology, it has an interlocking molecular structure that works to create a protective shield, so dirt can be washed away without compromising the quality of the paint or damaging the finish. It comes with a lifetime guarantee\* against peeling, flaking and blistering. Taubmans All Weather is a self-priming water based paint that has as a total UV blockout to protect the coating and substrate against the sun.



## USES

Exterior surfaces recommended include cement render, masonry, PVC piping, galvanised iron, steel, timber, trim, and roofs. Not suitable for use when the collection of drinking water is required

## FEATURES AND BENEFITS

<b>ADVANCED NANOGUARD® TECHNOLOGY</b>	Contains an interlocking molecular structure that creates a protective shield, so everyday dirt and stains can be wiped away without compromising the quality of the paint. It provides excellent mould and mildew protection - so you have a cleaner and healthier home environment
<b>SCRUB RESISTANT</b>	Provides a tough and durable abrasion-resistant coating
<b>ADVANCED WASHABILITY</b>	Resists burnishing – the formation of shiny patches on washing.
<b>MOULD RESISTANT</b>	Helps prevent the growth of mould, mildew and fungus in damp areas
<b>HIGH OPACITY</b>	Excellent hiding properties.
<b>EASY TO APPLY</b>	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
<b>ALL WEATHER PROTECTION</b>	Built with advanced UV protection technology to resists cracking & peeling from harsh weather conditions longer
<b>FLEXIBLE</b>	Withstands normal substrate movements
<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties

## DATASHEET

<b>DIRT SHEDDING FORMULA</b>	Protects surfaces and keeps them looking newer for longer by easily washing away dirt and pollutants from the surface
<b>SELF-PRIMING</b>	In most cases, removes the need for a prep coat
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our creation over a century ago in 1897 by George Henry Taubman, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success with our state-of-the-art plant in Clayton, VIC.
<b>TINTABLE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>AUSTRALIAN STANDARD</b>	A53730.8
<b>ADVANCED FLOW MODIFIERS</b>	Promotes ease of application, good flow properties and minimal roller splatter
<b>APAS APPROVED</b>	APAS 0280/3
<b>ACRYLIC BINDER</b>	Superior adhesion, flexibility, gloss retention & durability
<b>UV PROTECTION</b>	Blocks out harmful UV rays for longer lasting results
<b>WATER BASED FORMULA</b>	Easy clean up with water

## PRODUCT SPECIFICATIONS

<b>LOW SHEEN</b>	A subtle sheen level which is good for cleaning and hides surface imperfections better than gloss level paints.
<b>GLOSS LEVEL</b>	10-15 (% at a 60 degree angle)
<b>VOC LEVELS</b>	37g/Litre. Meets Green Building Council Requirements
<b>DRY TIMES: TOUCH DRY</b>	30 mins
<b>DRY TIMES: RECOAT</b>	2 hours
<b>1L AVAILABLE SIZES</b>	1l
<b>2L AVAILABLE SIZES</b>	2l
<b>4L AVAILABLE SIZES</b>	4l
<b>10L AVAILABLE SIZES</b>	10l
<b>15L AVAILABLE SIZES</b>	15l
<b>SDS</b>	SDS available at <a href="http://www.ppgmsds.com.au">www.ppgmsds.com.au</a>
<b>EXTENSIVE COLOUR RANGE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>WHITE BASE</b>	Tint your desired colour from a White base

## DATASHEET

<b>ACCENT BASE</b>	Tint your desired colour from an Accent base
<b>NEUTRAL BASE</b>	Tint your desired colour from a Neutral base
<b>BLACK BASE</b>	Tint your desired colour from a black base

## SURFACE PREPARATION

<b>GENERAL EXTERIOR</b>	Can include exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel
<b>NEW WORK</b>	<p><b>TIMBER</b></p> <p>Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar may require two coats or use Taubmans Oil Based Wood Primer.</p> <p><b>GALVANISED IRON</b></p> <p>Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with Z40 grade paper to remove chemical treatments and allow full adhesion.</p> <p><b>CEMENT RENDER / MASONRY</b></p> <p>Allow masonry, cement render and mortar to cure for 28 days before painting.</p> <p><b>STEEL</b></p> <p>Remove rust and prime with a suitable Taubmans iron &amp; steel primer or White Knight Rust Guard® Metal Primer.</p> <p><b>ZINCALUME® STEEL</b></p> <p>Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.</p>
<b>PREVIOUSLY PAINTED</b>	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
<b>TEMPERATURE MIN</b>	10 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>RECOATTEMPDEGREES</b>	25 (°C)
<b>RECOATHUMIDITYPERCENTAGE</b>	50 (%)
<b>SOFTWOOD TIMBER</b>	Ensure timber surface is dry, clean and free from dirt and debris prior to application

## APPLICATION

<b>WET FILM THICKNESS</b>	60 - 65 microns
<b>DRY FILM THICKNESS</b>	25 - 30 microns
<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
<b>BRUSH, ROLLER, SPRAY</b>	Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.

## DATASHEET

<b>NAP ROLLER</b>	10mm - 12mm Pile Roller
<b>COVERAGE</b>	16m <sup>2</sup> /litre.
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS</b>	10
<b>APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS</b>	35
<b>COATS REQUIRED</b>	Two minimum

## PRECAUTIONS

<b>GENERAL SAFETY INFORMATION</b>	<p><b>WALL PAINTS SAFETY</b></p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes; wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p> <p><b>CEILING SAFETY</b></p> <p>Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
<b>FIRST AID INFORMATION</b>	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a></p>
<b>ENVIRONMENT INFORMATION</b>	<p>Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a></p>

## ENVIRONMENT & SAFETY

<b>WARRANTY INFORMATION</b>	<p>Taubmans All Weather Exterior are guaranteed against blistering, flaking or peeling if applied on suitable and properly prepared surfaces according to printed directions. This guarantee applies to the owner of the house/property to which the paint has been applied for the duration that the owner owns the house/property to which the paint has been applied. The benefits provided under this guarantee are personal and are not transferable. This guarantee is given by PPG Industries Australia Pty Ltd. This guarantee applies to defects in the manufacture or formulation of the paint and does not cover paint failure caused by factors beyond our control. If this guarantee is not met, we will replace the paint or refund your money. We are not liable for the cost of labour or any other direct or indirect loss or damage arising from a breach of this guarantee. Customers are responsible for all costs of claiming under this guarantee. To claim, customers must write to us or call our Customer Care number to request a claim form. The benefits provided by this guarantee are in addition to other rights and remedies under the law. If you are a consumer within the meaning of the Australian Consumer Law: Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.</p>
-----------------------------	---

## VERSION

## DATASHEET

**VERSION NUMBER**

1.1

**VERSION DATE**

31 July 2024

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)