

## DATASHEET

# Taubmans Armawall Verona

# TAUBMANS

Product Code:  
305021


## Taubmans Armawall Verona

Taubmans Armawall Verona is a tough acrylic pigmented texture coating that contains aggregates and fillers to give a subtle, sandstone like finish with excellent impact resistance. Topcoat with Armawall Armashield, Armawall Roll On Membrane or Armawall Satin for enhanced durability and substrate protection.

## USES

Exterior cement render, masonry, fibrous cement sheeting, AAC panels and blocks, bricks and blockwork.

## FEATURES AND BENEFITS

<b>DURABILITY</b>	Excellent impact resistance
<b>FINISH</b>	Matt Finish – Contemporary finish that minimises surface imperfections
<b>STABLE BASE</b>	Can be applied as a single, coloured coat over Armawall Primer on suitable surfaces.
<b>FLEXIBLE</b>	Withstands normal substrate movements
<b>VAPOR PERMEABILITY</b>	Allows substrate to breathe to reduce moisture entrapment
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>WATER BASED FORMULA</b>	Easy clean up with water

## PRODUCT SPECIFICATIONS

<b>COLOUR RANGE</b>	Available in a wide range of colours
<b>PROFILE</b>	Low
<b>CLEAN UP</b>	Water, away from drains and watercourses

## DATASHEET

<b>VOLUME SOLIDS (%)</b>	55.1
<b>MATT</b>	<p>Can be applied to uneven surfaces in order to hide imperfections.</p> <p>May mark more easily than high sheen products, so is therefore not recommended for high traffic areas.</p> <p>Ideal for interior walls; an ultra-washable, stain resistant matt finish.</p> <p>Ideal for exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel. Not suitable for surfaces used to collect drinking water</p>
<b>DRY TIMES: TOUCH DRY</b>	60 mins
<b>DRY TIMES: RECOAT</b>	24 hours (Note: This may be lengthened in damp, cold or humid conditions. Do not apply at temperatures below 10°C.)
<b>15L AVAILABLE SIZES</b>	15L
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>
<b>EXTENSIVE COLOUR RANGE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>WHITE BASE</b>	Tint your desired colour from a White base

## Surface Preparation

<b>NEW CEMENT RENDER MASONRY &amp; CONCRETE (ARMAWALL)</b>	<p>New cement render, masonry and concrete surfaces should be allowed to cure for 28 days. Off form concrete should be thoroughly cleaned by acid etching, water or sand blasting to ensure all bond breaker oils are removed. Aged concrete masonry and fibro surfaces in sound condition should be scrubbed down with detergent and fresh water, fresh water washed and allowed to dry. Surface irregularities such as blow holes and profile defects may require patching with Armawall Smooth Patch or Armawall Coarse Patch prior to system application.</p>
--	---

## SURFACE PREPARATION

<b>SUBSTRATE MOISTURE CONTENT (ARMAWALL)</b>	Moisture content of the substrate must be no greater than 15% wood-moisture-equivalent (WME) prior to or during application, to ensure optimal coating system performance
--	---

## APPLICATION

<b>ODOUR</b>	Low
<b>APPLICATION</b>	This product is generally applied as one or two coats with a steel trowel and finished off with a plastic float or sponge. Two coats may be necessary to cover high spots on uneven surfaces. Product can also be sprayed or applied with a roller for different finish effects.
<b>GENERAL - ARMAWALL</b>	<p>The product information contained within this document is written by PPG Industries Australia Pty Ltd, as the manufacturer of Armawall Texture Coatings Range. PPG Industries Australia Pty Ltd recommends that you read and understand the information contained here in. In conjunction with the Data Sheet (DS), it is recommended that the product Material Safety Data Sheet (MSDS) is also read before you use or handle the product. The information contained in this data sheet is compiled as a result of extensive field and laboratory testing. For optimum performance of the Armawall Texture Coating System it is strongly recommended that the application is carried out by an applicator skilled in the Armawall systems and products. The Armawall Texture Range is not designed for use by non professional applicators or DIY use. Material warranties will only be issued when Armawall full systems have been employed and applied by skilled applicators in accordance with Armawall specific instructions and specifications. No warranty is implied or stated by the use of this Data Sheet, PPG Industries Australia Pty Ltd advises that it is a requirement for the home owner, builder, architect or main contractor to fully investigate the suitability of the Armawall Texture Range for it's desired use and application.</p>

## DATASHEET

<b>WET FILM THICKNESS</b>	0.6 -0.8 mm
<b>DRY FILM THICKNESS</b>	0.6 - 0.8 mm
<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
<b>NAP ROLLER</b>	Steel Trowel
<b>STAINLESS STEEL TROWEL, RED PLASTIC FLOAT</b>	Working in an upward action with the trowel, hold trowel & material against wall and evenly apply material. Now working in a tight circular motion with the RED PLASTIC FLOAT, Run the float over the surface, remember to keep the float FLAT on the wall to ensure even & smooth back the texture. Remember that the RED PLASTIC FLOAT will act as a razor and shave off any high areas of material. This can lead to some material wastage if the material is applied to thickly.
<b>STAINLESS STEEL TROWEL, TEXTURE SPRAY, ROLLER</b>	Yes
<b>COVERAGE</b>	1.4 m <sup>2</sup> /litre
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS</b>	10
<b>APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS</b>	35
<b>COATS REQUIRED</b>	One or Two

## PRECAUTIONS

<b>ENVIRONMENT INFORMATION ARMAWALL</b>	Do not pour leftover mixed render or any unused render powder down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>GENERAL SAFETY INFORMATION ARMAWALL</b>	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area above ground level. Do not store below 5 deg C temperature. Do not keep open bags. These should be disposed of.
<b>FIRST AID INFORMATION</b>	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a></p>

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)