

DATASHEET

Taubmans Professional Ceiling

TAUBMANS

Product Code:
278000



Taubmans Professional Ceiling

Taubmans Professional Ceiling is specifically designed to give a dead flat finish which hides surface imperfections and also minimises banding on new plasterboard. It is easy to apply with minimum splatter and has high opacity.

USES

Ideal for interior & exterior sheltered ceilings

FEATURES AND BENEFITS

FLAT FINISH	Gives a flat finish with excellent surface defect hiding properties.
HIGH OPACITY	Excellent hiding properties.
WATER BASED FORMULA	Easy clean up with water
FAST DRYING	Assist project completion timelines with fast drying properties
EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.

PRODUCT SPECIFICATIONS

FLAT	Designed to produce flat uniform finish with no roller marks
GLOSS LEVEL	1-2 (% at a 60 degree angle)
VOC LEVELS	30g/Litre
DRY TIMES: TOUCH DRY	30 mins

DATASHEET

DRY TIMES: RECOAT	2 hours
15L AVAILABLE SIZES	15L
SDS	SDS available from the Taubmans Website taubmans.com.au
EXTENSIVE COLOUR RANGE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
WHITE BASE	Tint your desired colour from a White base
DRY FILM THICKNESS	25 - 30 microns
WET FILM THICKNESS	60 - 65 microns

SURFACE PREPARATION

PREVIOUSLY PAINTED	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
---------------------------	--

APPLICATION

BRUSH, ROLLER, SPRAY	Apply two coats by roller, brush or spray gun, with 2 hours between each coat. Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
NAP ROLLER	10mm - 12mm Pile Roller
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
CURING	Avoid exposure to steam and condensation for 48 hours after painting.
COVERAGE	Up to 16m ² /litre, depending on the nature of the surface. Coverage on rough or absorbent surfaces will be lower. The first coat on gyprock will be approx 10m ² /litre.
APPLICATION TEMPERATURE MINIMUM DEGREES CELSIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELSIUS	35
COATS REQUIRED	2

PRECAUTIONS

GENERAL SAFETY INFORMATION	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use
FIRST AID INFORMATION	IF SWALLOWED Do NOT induce vomiting. Seek medical advice immediately. EYE CONTACT

DATASHEET

Flush with plenty of water. Always seek medical advice.

SKIN CONTACT

Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION

Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA

24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au