

DATASHEET

# Taubmans Armawall Primer

# TAUBMANS

Product Code:  
315500



## Taubmans Armawall Primer

Taubmans Armawall Primer is a water based acrylic primer/sealer designed for both new and previously painted surfaces. It has been specifically designed to penetrate the surface to promote excellent adhesion and even out the absorption rate of the substrate. Taubmans Armawall Primer has excellent efflorescence resistance making it ideal for use over most masonry surfaces.

Taubmans Armawall Primer is suitable for use on both new and previously painted surfaces.

## USES

Priming & sealing of most masonry surfaces including, cement render, acrylic modified cement render, AAC blocks and panels, brickwork, fibrous cement sheeting etc. Particularly suitable for repaint situations.

Not suitable for use on Tilt-up concrete, GRC and CFC sheeting. Taubmans Armawall Sealer/Bonder (Solvent Based) is recommended for these applications

## FEATURES AND BENEFITS

<b>ALKALI RESISTANCE</b>	Helps to prevent alkali attack common in new masonry
<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>PENETRATIVE FORMULA</b>	Low viscosity and excellent wetting properties allow the coating to penetrate the surface.
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our creation over a century ago in 1897 by George Henry Taubman, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success with our state-of-the-art plant in Clayton, VIC.
<b>APAS APPROVED</b>	APAS Spec.:- APAS 0117/2; Australian Standard AS 2311.
<b>WATER BASED FORMULA</b>	Easy clean up with water

## PRODUCT SPECIFICATIONS

<b>VOLUME SOLIDS (%)</b>	38
--------------------------	----

## DATASHEET

<b>WHITE BASE</b>	Do not tint
<b>VOC LEVELS</b>	26g/Litre
<b>DRY TIMES: TOUCH DRY</b>	30 mins
<b>DRY TIMES: RECOAT</b>	2 hours
<b>SDS</b>	SDS available at <a href="http://www.ppgmsds.com.au">www.ppgmsds.com.au</a>
<b>SIZES AVAILABLE</b>	15L

## SURFACE PREPARATION

<b>SURFACE PREPARATION</b>	<p>Ensure the surface is clean and dry. All surfaces must be free of dirt, dust, grease, oil, mould release agents, bond breakers and any other contaminants that may interfere with adhesion.</p> <p>Exposed metal on the surface, should be removed or treated against corrosion.</p>
----------------------------	---

## Surface Preparation

<b>PREVIOUSLY PAINTED (ARMAWALL)</b>	<p>Wash down all surfaces to remove any loose, powdery, flaky material or any other surface contaminants that may be present. Allow to dry. Apply Armawall Primer undiluted by brush, roller or spray to the surface prior to applying the specified Armawall Texture Coating System.</p>
<b>NEW CEMENT RENDER MASONRY &amp; CONCRETE</b>	<p>Fresh cementitious substrates should be left to cure for 28 days before painting. There must be less than 15% moisture content at the surface prior to and during application.</p> <p>All surfaces must be free of dirt, dust, grease, oil, mould release agents, bond breakers and any other contaminants that may interfere with adhesion.</p> <p>Surface irregularities such as blow holes and profile defects may require patching with Armawall Smooth Patch or Armawall Coarse Patch prior to system application.</p> <p>Note: this product is not suitable for Tilt Up Concrete, Glass Reinforced Concrete (GRC) or Compressed Fibre Cement (CFC). Armawall Sealer Bonder is recommended for these substrates.</p>

## APPLICATION

<b>FINISHING</b>	<p>This product is a surface preparation product only, as such it should be used in conjunction with the complete Armawall Texture System and specification. As a surface preparation product it should not be left exposed for more than 14 days after application. The finishing system should be applied in a continual time frame, please refer to the Armawall Product Data Sheet for drying times.</p>
<b>ARMAWALL PRIMER APP</b>	<p>To maximise adhesion of membrane topcoats, good penetration of Armawall Primer is essential. On masonry substrates, Armawall Primer can be thinned by 10-25% with water prior to application to assist with penetration into the substrate. Armawall Primer can be applied using a roller, brush or spray.</p>
<b>WET FILM THICKNESS</b>	100 - 125 microns
<b>DRY FILM THICKNESS</b>	38 - 48 microns (undiluted)
<b>NAP ROLLER</b>	15-22mm synthetic or sheepskin

## DATASHEET

<b>COVERAGE</b>	8 - 10 m <sup>2</sup> /litre
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS</b>	10
<b>APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS</b>	35
<b>COATS REQUIRED</b>	One
<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. Continue stirring at regular intervals during application.

## PRECAUTIONS

<b>GENERAL SAFETY INFORMATION</b>	<b>WALL PAINTS SAFETY</b>	Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes; wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.
	<b>CEILING SAFETY</b>	Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.
<b>FIRST AID INFORMATION</b>	<b>IF SWALLOWED</b>	- Do NOT induce vomiting. Seek medical advice immediately.
	<b>EYE CONTACT</b>	- Flush with plenty of water. Always seek medical advice.
	<b>SKIN CONTACT</b>	- Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.
	<b>INHALATION</b>	- Remove to fresh air, seek medical advice if breathing is laboured.
		AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a>
<b>ENVIRONMENT INFORMATION</b>	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a>	

## VERSION

<b>VERSION DATE</b>	9 September 2025
<b>VERSION NUMBER</b>	1.1

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

DATASHEET

**CUSTOMER SERVICE/COMPANY CONTACT**

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)