

DATASHEET

Taubmans Armawall Ultrafine

TAUBMANS

Product Code:
310200


Taubmans Armawall Ultrafine

Taubmans Armawall Ultrafine is a durable exterior matt acrylic finish designed to give a cement render effect and bridge hairline cracks in masonry surfaces. It can left as a matt finish or it can be over coated with Armawall Armashield or Armawall Satin for extra durability and substrate protection. Armawall Ultrafine does not require primer except on Tilt Slab or CFC.

USES

Brick, fibro, masonry, cement render, AAC panels and blocks and other masonry surfaces. DO NOT use on timber surfaces.

FEATURES AND BENEFITS

LOW TEXTURE PROFILE	Contemporary render-like finish
NO PRIMER REQUIRED	Economical 2 coat system rather than the usual 3 coat texture systems
APAS APPROVED	APAS 0117/3
LOW VOC	Contains low level of VOC to conform to requirements of Green Building Council of Australia (GBCA).
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
WATER BASED FORMULA	Easy clean up with water

PRODUCT SPECIFICATIONS

PROFILE	Low
CLEAN UP	Water, away from drains and watercourses
MATT	Can be applied to uneven surfaces in order to hide imperfections. May mark more easily than high sheen products, so is therefore not recommended for high traffic areas. Ideal for interior walls; an ultra-washable, stain resistant matt finish.

DATASHEET

Ideal for exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel. Not suitable for surfaces used to collect drinking water

LOW SHEEN	A subtle sheen level which is good for cleaning and hides surface imperfections better than gloss level paints.
GLOSS LEVEL	5-6 at 60° (% at a 60 degree angle)
VOC LEVELS	<50%
DRY TIMES: TOUCH DRY	60 mins
DRY TIMES: RECOAT	4 hours (Note: This may be lengthened in damp, cold or humid conditions. Do not apply at temperatures below 10°C)
15L AVAILABLE SIZES	15L
SDS	SDS available from the Taubmans Website taubmans.com.au
EXTENSIVE COLOUR RANGE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
WHITE BASE	Tint your desired colour from a White base
ACCENT BASE	Tint your desired colour from an Accent base

Surface Preparation

GENERAL-ARMAWALL	Surface preparation is the responsibility of the Applicator, Builder, Renovator or Main Contractor. Armawall Surface Preparation Products are designed to perform at their optimum when used as part of an Armawall Texture Coating System.
-------------------------	---

SURFACE PREPARATION

MASONRY SURFACES	New cement render, masonry and concrete surfaces should be allowed to cure for 28 days. Off form concrete should be thoroughly cleaned by acid etching, water or sand blasting to ensure all bond breaker oils are removed. Seal tilt slab concrete and CFC with Armawall Sealer/Bonder thinned 50% with i coat LO - 2 Thinner to ensure adhesion of topcoats. Previously painted surfaces in sound condition should be scrubbed down with detergent and fresh water, fresh water washed and allowed to dry. Previously painted enamel surfaces should be undercoated with Taubmans Tradecoat. Surface irregularities such as blow holes and profile defects may require patching with Armawall Smooth or Coarse Patch prior to system application. CAUTION: When applying Armawall Ultrafine on large tilt-up concrete slabs or unbroken high rise off form concrete, you will not easily be able to maintain a wet edge. This can cause overlaps to stand out.
SUBSTRATE MOISTURE CONTENT (ARMAWALL)	Moisture content of the substrate must be no greater than 15% wood-moisture-equivalent (WME) prior to or during application, to ensure optimal coating system performance
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)

DATASHEET

APPLICATION

ODOUR	Low
APPLICATION	Armawall Ultrafine does not require primer except on Tilt Slab or CFC. Apply 2 coats of Armawall Ultrafine using a long nap roller
WET FILM THICKNESS	140 -150 microns
DRY FILM THICKNESS	90 - 100 microns
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
BRUSH, ROLLER	Apply one or two coats (as per recommendation) by brush or roller, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
COARSE TEXTURE ROLLER	Yes
NAP ROLLER	Long Nap Roller
COVERAGE	8 m ² /litre
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
COATS REQUIRED	One or Two

PRECAUTIONS

GENERAL SAFETY INFORMATION	<p>WALL PAINTS</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p> <p>CEILING</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
FIRST AID INFORMATION	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au</p>
ENVIRONMENT INFORMATION	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DATASHEET

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au