

## DATASHEET

# Taubmans Tradex Ceiling

# TAUBMANS

Product Code:  
274000


## Taubmans Tradex Ceiling

Tradex Ceiling White is specifically designed to give a dead flat finish which hides surface imperfections and minimises banding on new plaster board. It is easy to apply with minimum splatter and has high opacity. Ideal for new and repainting ceilings.

## USES

Interior and sheltered exterior ceilings

## FEATURES AND BENEFITS

|                                |                                                                                                                                                                                                                                 |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>HIGH OPACITY</b>            | Excellent hiding properties.                                                                                                                                                                                                    |
| <b>EASY TO APPLY</b>           | Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.                                                                                                                                               |
| <b>FLAT FINISH</b>             | Gives a flat finish with excellent surface defect hiding properties.                                                                                                                                                            |
| <b>FAST DRYING</b>             | Assist project completion timelines with fast drying properties                                                                                                                                                                 |
| <b>AUSTRALIAN MADE</b>         | Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC. |
| <b>TINTABLE</b>                | Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>                             |
| <b>AUSTRALIAN STANDARD</b>     | AS2311, AS3730.1                                                                                                                                                                                                                |
| <b>ADVANCED FLOW MODIFIERS</b> | Promotes ease of application, good flow properties and minimal roller splatter                                                                                                                                                  |
| <b>APAS NUMBER</b>             | APAS 0260/5                                                                                                                                                                                                                     |
| <b>WATER BASED FORMULA</b>     | Easy clean up with water                                                                                                                                                                                                        |

## PRODUCT SPECIFICATIONS

## DATASHEET

|                             |                                                                                              |
|-----------------------------|----------------------------------------------------------------------------------------------|
| <b>DRY FILM THICKNESS</b>   | 25 - 30 microns                                                                              |
| <b>WET FILM THICKNESS</b>   | 60 - 65 microns                                                                              |
| <b>FLAT</b>                 | Designed to produce flat uniform finish with no roller marks                                 |
| <b>GLOSS LEVEL</b>          | 1-2 (% at a 60 degree angle)                                                                 |
| <b>VOC LEVELS</b>           | 30g/Litre                                                                                    |
| <b>DRY TIMES: TOUCH DRY</b> | 30 mins                                                                                      |
| <b>DRY TIMES: RECOAT</b>    | 2 hours                                                                                      |
| <b>4L AVAILABLE SIZES</b>   | 4l                                                                                           |
| <b>10L AVAILABLE SIZES</b>  | 10l                                                                                          |
| <b>15L AVAILABLE SIZES</b>  | 15l                                                                                          |
| <b>SDS</b>                  | SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a> |
| <b>WHITE BASE</b>           | Tint your desired colour from a White base                                                   |

## SURFACE PREPARATION

|                           |                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------|
| <b>PREVIOUSLY PAINTED</b> | Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion. |
|---------------------------|----------------------------------------------------------------------------------------------------------------------|

## APPLICATION

|                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>STIRRING</b>                                            | Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency |
| <b>BRUSH, ROLLER, SPRAY</b>                                | Apply two coats by roller, brush or spray gun, with 2 hours between each coat. Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.                                                                                                                                                                                                                           |
| <b>NAP ROLLER</b>                                          | 10mm - 12mm Pile Roller                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>CURING</b>                                              | Avoid exposure to steam and condensation for 48 hours after painting.                                                                                                                                                                                                                                                                                                                                                                       |
| <b>COVERAGE</b>                                            | Up to 16m <sup>2</sup> /litre.                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>APPLICATION TEMPERATURE<br/>MINIMUM DEGREES CELCIUS</b> | 10                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>APPLICATION TEMPERATURE<br/>MAXIMUM DEGREES CELCIUS</b> | 35                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>COATS REQUIRED</b>                                      | Two                                                                                                                                                                                                                                                                                                                                                                                                                                         |

## DATASHEET

### PRECAUTIONS

|                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>GENERAL SAFETY INFORMATION</b> | Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>FIRST AID INFORMATION</b>      | <p>IF SWALLOWED</p> <p>Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT</p> <p>Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT</p> <p>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION</p> <p>Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA</p> <p>24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a></p> |
| <b>ENVIRONMENT INFORMATION</b>    | Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a>                                                                                                                                                                                                                                                                                                            |

### DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

### CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)