

DATASHEET

# Taubmans Endure Interior Low Sheen (124200, 124204, 124205)

# TAUBMANS

Product Code:  
124200



## Taubmans Endure Interior Low Sheen (124200, 124204, 124205)

Taubmans Endure Interior Walls protects homes against the growth of mould, mildew and bacteria with advanced anti-microbial technology. Nanoguard® Advanced Technology with interlocking particles ensures it is exceptionally scrub and stain resistant and easy to wash, leaving your walls cleaner and healthier for longer. It also offers a lifetime maximum protection guarantee\*.



## USES

Proven to deliver superior protection, Ideal for all interior walls.

## FEATURES AND BENEFITS

<b>LOW VOC PRODUCT</b>	Contains low level of VOC to conform to requirements of Green Building Council of Australia (GBCA). Excludes HiChroma bases.
<b>ADVANCED NANO GUARD® TECHNOLOGY</b>	Contains an interlocking molecular structure that creates a protective shield, so everyday dirt and stains can be wiped away without compromising the quality of the paint. It provides excellent mould and mildew protection - so you have a cleaner and healthier home environment
<b>SCRUB RESISTANT</b>	Provides a tough and durable abrasion-resistant coating
<b>STAIN RESISTANT</b>	Stains can be easily wiped away without compromising the original quality of the paint
<b>ADVANCED WASHABILITY</b>	Resists burnishing – the formation of shiny patches on washing.
<b>ASTHMA &amp; ALLERGY FRIENDLY</b>	Approved by the National Asthma Council Australia's Sensitive Choice® program. Products approved by the Sensitive Choice Program may help people with asthma and allergies
<b>MOULD RESISTANT</b>	Helps prevent the growth of mould, mildew and fungus in damp areas
<b>BACTERIA-SHIELD PROTECTION</b>	Neutralises and inhibits the growth of common bacteria and germs such as Staphylococcus aureus and Escherchia coli. The built-in technology lasts the life of the paint, doesn't wash or wear off and improves indoor air quality.
<b>HIGH OPACITY</b>	Excellent hiding properties.
<b>EASY TO APPLY</b>	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.

## DATASHEET

<b>NON YELLOWING FORMULA</b>	Technologically advanced non-yellowing formula
<b>FLEXIBLE</b>	Withstands normal substrate movements
<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>DIRT SHEDDING FORMULA</b>	Protects surfaces and keeps them looking newer for longer by easily washing away dirt and pollutants from the surface
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>TINTABLE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>AUSTRALIAN STANDARD</b>	AS3730.3, AS2311
<b>ADVANCED FLOW MODIFIERS</b>	Promotes ease of application, good flow properties and minimal roller splatter
<b>APAS APPROVED</b>	APAS 0260/3
<b>ACRYLIC BINDER</b>	Superior adhesion, flexibility, gloss retention & durability
<b>WATER BASED FORMULA</b>	Easy clean up with water

## PRODUCT SPECIFICATIONS

<b>LOW SHEEN</b>	A subtle sheen level which is good for cleaning and hides surface imperfections better than gloss level paints.
<b>GLOSS LEVEL</b>	5-8 (% at a 60 degree angle)
<b>VOC LEVELS</b>	<5g/Litre
<b>DRY TIMES: TOUCH DRY</b>	30 mins
<b>DRY TIMES: RECOAT</b>	2 hours
<b>1L AVAILABLE SIZES</b>	1l
<b>2L AVAILABLE SIZES</b>	2l
<b>4L AVAILABLE SIZES</b>	4l
<b>6L AVAILABLE SIZES</b>	6l
<b>10L AVAILABLE SIZES</b>	10l
<b>15L AVAILABLE SIZES</b>	15l
<b>SDS</b>	SDS available at <a href="http://www.ppgmsds.com.au">www.ppgmsds.com.au</a>

## DATASHEET

<b>EXTENSIVE COLOUR RANGE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>WHITE BASE</b>	Tint your desired colour from a White base
<b>ACCENT BASE</b>	Tint your desired colour from an Accent base
<b>NEUTRAL BASE</b>	Tint your desired colour from a Neutral base
<b>HI-CHROMA RED BASE</b>	Tint your desired colour from a red base
<b>HI-CHROMA YELLOW BASE</b>	Tint your desired colour from a yellow base
<b>HI-CHROMA BLUE BASE</b>	Tint your desired colour from a blue base

## SURFACE PREPARATION

<b>AFTER PAINTING</b>	Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.
<b>TEMPERATURE MIN</b>	10 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>RECOATTEMPDEGREES</b>	25 (°C)
<b>RECOATHUMIDITYPERCENTAGE</b>	50 (%)
<b>NEW/BAREWORK</b>	Seal bare wallboards with Taubmans 3in1. Seal set plaster with Prep Right (Acrylic) Plaster Sealer.
<b>REPAINT</b>	Remove all loose and flaking paint. Wash off dirt, grease. Fill holes and cracks with a suitable filler. If mould is present treat surface with bleach solution then wash off with clean water and allow to dry. Spot bare substrate in accordance with directions for new work.

## APPLICATION

<b>WET FILM THICKNESS</b>	60 - 65 microns
<b>DRY FILM THICKNESS</b>	25 - 30 microns
<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
<b>BRUSH, ROLLER, SPRAY</b>	Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
<b>NAP ROLLER</b>	10mm Pile Roller
<b>CURING</b>	Avoid exposure to steam and condensation for 48 hours after painting.
<b>COVERAGE</b>	Up to 16m <sup>2</sup> /litre.

## DATASHEET

**APPLICATION TEMPERATURE** 10

**MINIMUM DEGREES CELCIUS**

**APPLICATION TEMPERATURE** 35

**MAXIMUM DEGREES CELCIUS**

**COATS REQUIRED** Two

## PRECAUTIONS

### GENERAL SAFETY INFORMATION

WALL PAINTS

SAFETY

Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

CEILING

SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

### FIRST AID INFORMATION

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686  
Further information: [www.taubmans.com.au](http://www.taubmans.com.au)

### ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit [paintback.com.au](http://paintback.com.au)

## ENVIRONMENT & SAFETY

### WARRANTY INFORMATION

Taubmans Endure is guaranteed against blistering, flaking or peeling if applied on suitable and properly prepared surfaces according to printed directions. This guarantee applies to the owner of the house/property to which the paint has been applied and is available as long as the owner owns and lives in the house/property. The benefits provided under this guarantee are not transferable. Proof of purchase is required. This guarantee is given by PPG Industries Australia Pty Ltd. This guarantee only applies to residential properties within Australia. This guarantee applies to defects in the manufacture or formulation of the paint and does not cover paint failure caused by factors beyond our control. If this guarantee is not met, we will replace the paint or refund your money. We are not liable for the cost of labour or any other direct or indirect loss or damage arising from a breach of this guarantee. Customers are responsible for all costs of claiming under this guarantee.

To claim, customers must write to us or call our Customer Service number to request a claim form. The benefits provided by this guarantee are in addition to other rights and remedies under the law. If you are a consumer within the meaning of the Australian Consumer Law: Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure

### LOW VOLATILE ORGANIC COMPOUND

Helps to improve indoor air quality

## VERSION

## DATASHEET

**VERSION NUMBER**

1.1

**VERSION DATE**

8 March 2024

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)