

DATASHEET

Taubmans Water Based Enamel Semi Gloss (121410, 121414, 121415)

TAUBMANS

Product Code:
121410



Taubmans Water Based Enamel Semi Gloss (121410, 121414, 121415)

Premium water based enamel with Low VOC specially designed to protect doors, trims, skirting boards and windows. Incorporating LTA+ technology, Taubmans Water Based Enamel provides a smooth, washable and abrasion resistant finish.

INTERIOR ENAMEL • Easy water clean up • Inhibits mould & mildew • Asthma & Allergy Friendly
• Non-yellowing formula • Microban® product protection • Low VOC



USES

Suitable for all interior and exterior doors, trims and windows.

FEATURES AND BENEFITS

APAS APPROVED	APAS 0260/2
SCRUB RESISTANT	Provides a tough and durable abrasion-resistant coating
ADVANCED WASHABILITY	Resists burnishing – the formation of shiny patches on washing.
LOW VOC	Contains low level of VOC to conform to requirements of Green Building Council of Australia (GBCA).
ASTHMA & ALLERGY FRIENDLY	Approved by the National Asthma Council Australia's Sensitive Choice® program. Products approved by the Sensitive Choice Program may help people with asthma and allergies
MOULD RESISTANT	Helps prevent the growth of mould, mildew and fungus in damp areas
HIGH OPACITY	Excellent hiding properties.
EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
NON YELLOWING FORMULA	Technologically advanced non-yellowing formula
ALL WEATHER PROTECTION	Built with advanced UV protection technology to resists cracking & peeling from harsh weather conditions longer

DATASHEET

INTERNAL AND EXTERNAL	Suitable for use in internal and external areas
FLEXIBLE	Withstands normal substrate movements
FAST DRYING	Assist project completion timelines with fast drying properties
AUSTRALIAN MADE	Our Aussie Heritage: Since our creation over a century ago in 1897 by George Henry Taubman, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success with our state-of-the-art plant in Clayton, VIC.
TINTABLE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
AUSTRALIAN STANDARD	AS2311, AS3730.2
ACRYLIC BINDER	Superior adhesion, flexibility, gloss retention & durability
WATER BASED FORMULA	Easy clean up with water

PRODUCT SPECIFICATIONS

SEMI GLOSS	Offers good stain resistance and is easy to clean for high traffic areas that are subject to wear and tear. Ideal for all interior walls, bathrooms, laundries, doors and high traffic areas. Ideal for exterior walls (recommended for weatherboards, roofs and trim), cement render / masonry, timber, galvanised iron, PVC piping and steel. Not suitable for surfaces used to collect drinking water
GLOSS LEVEL	40-50 at 60° (% at a 60 degree angle)
VOC LEVELS	<49g/Litre Meets Green Building Council Australia requirements
DRY TIMES: TOUCH DRY	30 mins
DRY TIMES: RECOAT	2 hours
1L AVAILABLE SIZES	1L
2L AVAILABLE SIZES	2L
4L AVAILABLE SIZES	4L
10L AVAILABLE SIZES	10L
SDS	SDS available at www.ppgmsds.com.au
EXTENSIVE COLOUR RANGE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
WHITE BASE	Tint your desired colour from a White base
ACCENT BASE	Tint your desired colour from an Accent base
NEUTRAL BASE	Tint your desired colour from a Neutral base

DATASHEET

SURFACE PREPARATION

NEW WORK	<p>TIMBER</p> <p>Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar may require two coats or use Taubmans Oil Based Wood Primer.</p> <p>GALVANISED IRON</p> <p>Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting.</p> <p>For structural galvanised iron, abrade with 240 grade paper to remove chemical treatments and allow full adhesion. Apply one coat of Taubmans 3 in 1 Prep.</p> <p>CEMENT RENDER / MASONRY</p> <p>Allow masonry, cement render and mortar to cure for 28 days before painting. Apply one coat of Taubmans 3 in 1 Prep.</p> <p>STEEL</p> <p>Remove rust and prime with a suitable Taubmans iron & steel primer or White Knight Rust Guard® Metal Primer.</p> <p>ZINCALUME® STEEL</p> <p>Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.</p>
GENERAL INTERIOR	Can include interior walls, ceilings, doors and architraves
GENERAL EXTERIOR	Can include exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel
PREVIOUSLY PAINTED	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
AFTER PAINTING	Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)

APPLICATION

BRUSH, ROLLER, SPRAY	Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality 5mm nap roller.
WET FILM THICKNESS	60 -65 microns
DRY FILM THICKNESS	25 - 30 microns
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
NAP ROLLER	5mm Pile Roller
CURING	Avoid exposure to steam and condensation for 48 hours after painting.
COVERAGE	Up to 16m ² /litre.

DATASHEET

APPLICATION TEMPERATURE 10

MINIMUM DEGREES CELCIUS

APPLICATION TEMPERATURE 35

MAXIMUM DEGREES CELCIUS

COATS REQUIRED Two

PRECAUTIONS

GENERAL SAFETY INFORMATION

WALL PAINTS

SAFETY

Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

CEILING

SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

FIRST AID INFORMATION

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686
Further information: www.taubmans.com.au

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

VERSION

VERSION NUMBER 1.2

VERSION DATE 26 July 2024

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au