

## DATASHEET

# Taubmans Professional Undercoat

# TAUBMANS

Product Code:  
278500


## Taubmans Professional Undercoat

Taubmans Professional Undercoat is a high-density, water-based all-purpose sealer with outstanding hiding, filling, and sanding properties. It is rapid drying with fast recoat for water and oil-based finishes.

## USES

Ideal for new / repainted interior and exterior surfaces as an undercoat / sealer. Interior surfaces as an undercoat directly over bare timber or as a sealer for wallboards.

## FEATURES AND BENEFITS

<b>INTERNAL AND EXTERNAL</b>	Suitable for use in internal and external areas
<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>EASY TO APPLY</b>	Holds a wet edge for longer and reduces roller splatter
<b>AUSTRALIAN MADE</b>	Taubmans has been used to paint Australian homes since 1899. We continue to keep George Henry Taubmans legacy alive by manufacturing paint in Australia at our Villawood (NSW) and Clayton (VIC) plants. Our paints are engineered by Australians to withstand Australia's unique conditions
<b>HIGH OPACITY</b>	Superior hiding properties
<b>ACRYLIC BINDER</b>	Increases adhesion, flexibility and permeability
<b>WATER BASED FORMULA</b>	Easy clean up with water

## PRODUCT SPECIFICATIONS

<b>VOC LEVELS</b>	39g/Litre
<b>DRY TIMES: TOUCH DRY</b>	30 mins
<b>DRY TIMES: RECOAT</b>	2 hours

## DATASHEET

<b>4L AVAILABLE SIZES</b>	4L
<b>10L AVAILABLE SIZES</b>	10L
<b>15L AVAILABLE SIZES</b>	15L
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>
<b>WHITE BASE</b>	Tint your desired colour from a White base

## SURFACE PREPARATION

<b>WET FILM THICKNESS</b>	60 - 65 microns (Microns)
<b>DRY FILM THICKNESS</b>	25 - 30 microns (Microns)
<b>AFTER PAINTING</b>	Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.
<b>TEMPERATURE MIN</b>	10 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>RECOATTEMPDEGREES</b>	25 (°C)
<b>RECOATHUMIDITYPERCENTAGE</b>	50 (%)

## APPLICATION

<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
<b>BRUSH, ROLLER, SPRAY</b>	Apply two coats by roller, brush or spray gun, with 2 hours between each coat. Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
<b>CURING</b>	Avoid exposure to steam and condensation for 48 hours after painting.
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELSIUS</b>	10
<b>APPLICATION TEMPERATURE MAXIMUM DEGREES CELSIUS</b>	35
<b>COATS REQUIRED</b>	1
<b>COVERAGE</b>	Up to 16m <sup>2</sup> /litre on sealed or impervious surfaces. Spreading rate will be lower on rough or absorbent surfaces. Coverage on bare paper faced plasterboard will be Up to 8m <sup>2</sup> /litre.

## PRECAUTIONS

<b>GENERAL SAFETY INFORMATION</b>	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use
---------------------------------------	--

## DATASHEET

### FIRST AID INFORMATION

#### IF SWALLOWED

Do NOT induce vomiting. Seek medical advice immediately.

#### EYE CONTACT

Flush with plenty of water. Always seek medical advice.

#### SKIN CONTACT

Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

#### INHALATION

Remove to fresh air, seek medical advice if breathing is laboured.

#### AUSTRALIA

24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)

### ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit [paintback.com.au](http://paintback.com.au)

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)