

## DATASHEET

# Taubmans Armawall Interior Flat

# TAUBMANS

Product Code:  
310000


## Taubmans Armawall Interior Flat

Taubmans Armawall Interior Flat is a high build acrylic coating designed for interior or undercover ceilings and balcony soffits. Armawall Interior Flat produces a high build stipple finish which hides minor surface defects on ceilings.

## USES

Plasterboard, cement render, AAC panels, masonry and fibrous cement interior or undercover surfaces. Recommended for defect hiding on ceilings.

## FEATURES AND BENEFITS

<b>LOW VOC</b>	Contains low level of VOC to conform to requirements of Green Building Council of Australia (GBCA).
<b>HIGH OPACITY</b>	Excellent hiding properties.
<b>FLEXIBLE</b>	Withstands normal substrate movements
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>AUSTRALIAN STANDARD</b>	AS4548.3
<b>WATER BASED FORMULA</b>	Easy clean up with water

## PRODUCT SPECIFICATIONS

<b>GLOSS LEVEL</b>	1-2 at 60° (% at a 60 degree angle)
<b>VOC LEVELS</b>	< 50g/Litre
<b>DRY TIMES: TOUCH DRY</b>	30 mins
<b>DRY TIMES: RECOAT</b>	4 hours. This may be lengthened in damp, cold or humid conditions

## DATASHEET

<b>15L AVAILABLE SIZES</b>	15L
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>
<b>EXTENSIVE COLOUR RANGE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>WHITE BASE</b>	Tint your desired colour from a White base
<b>PROFILE</b>	Low or Medium featuring fine stipple peaks

## SURFACE PREPARATION

<b>MASONRY SURFACES</b>	New cement render, masonry and concrete surfaces should be allowed to cure for 28 days. Off form concrete should be thoroughly cleaned by acid etching, water or sand blasting to ensure all bond breaker oils are removed. All surfaces should be primed with Armawall Primer (thinned 50-100% with water) prior to the application of Armawall Interior Flat. Seal tilt slab concrete with Armawall Sealer/ Bonder to ensure adhesion of topcoats. Previously painted surfaces in sound condition should be scrubbed down with detergent and fresh water, fresh water washed and allowed to dry. Surface irregularities such as blow holes and profile defects may require patching with Armawall Smooth Patch or Armawall Coarse Patch prior to system application. Refer individual data sheets for further information.
<b>SUBSTRATE MOISTURE CONTENT (ARMAWALL)</b>	Moisture content of the substrate must be no greater than 15% wood-moisture-equivalent (WME) prior to or during application, to ensure optimal coating system performance

## APPLICATION

<b>WET FILM THICKNESS</b>	240 - 250 microns
<b>DRY FILM THICKNESS</b>	140 - 150 microns
<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
<b>AIRLESS SPRAY</b>	AIRLESS SPRAY
<b>NAP ROLLER</b>	Texture Roller 16 - 22mm
<b>COVERAGE</b>	2m <sup>2</sup> /litre
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS</b>	10
<b>APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS</b>	35
<b>COATS REQUIRED</b>	One or Two
<b>ODOUR</b>	Low
<b>APPLICATION</b>	Armawall Interior Flat is normally applied by airless spray to achieve the high build required. To obtain the desired level of texture, the wet coat is laid off with the appropriate texture roller. The product may also be applied directly as a two coat system.

## DATASHEET

### PRECAUTIONS

<b>GENERAL SAFETY INFORMATION ARMAWALL</b>	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area above ground level. Do not store below 5 deg C temperature. Do not keep open bags. These should be disposed of.
<b>FIRST AID INFORMATION</b>	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a></p>
<b>ENVIRONMENT INFORMATION</b>	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a>

### DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

### CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)