

DATASHEET

Taubmans TAUBMANS EASYCOAT CEILINGS

TAUBMANS

Product Code:
199000



TAUBMANS EASYCOAT CEILINGS

The Taubmans® EASYCOAT® interior range has been designed with a family home in mind. With Microban® technology, EASYCOAT protects against the growth of bacteria, mould and fungus, making it ideal for damp and humid areas like the kitchen, bathroom and laundry.

EASYCOAT is also low in VOCs, which means it has minimal impact on the indoor air quality, and it is low in odour. Add the approval from Sensitive Choice® for asthma and allergy friendly products, and it's easy to see why EASYCOAT is the safe family choice.

USES

All Interior Ceilings including damp and humid areas like the kitchen, bathroom and laundry.

FEATURES AND BENEFITS

ASTHMA & ALLERGY FRIENDLY	Approved by the National Asthma Council Australia's Sensitive Choice® program. Products approved by the Sensitive Choice Program may help people with asthma and allergies
MOULD RESISTANT	Helps prevent the growth of mould, mildew and fungus in damp areas
MICROBAN	EASYCOAT with Microban® technology helps to protect painted surfaces from the growth of bacteria, mould and fungus. These built-in antimicrobial properties make EASYCOAT ideal for walls and ceilings in bedrooms, kitchens and bathrooms, as well as damp, high humidity areas. Microban technology is limited to the treated surface and is not designed to protect users or others from disease-causing microorganisms. Microban is not a substitute for normal cleaning practices.
EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
FLAT FINISH	Gives a flat finish with excellent surface defect hiding properties.
FAST DRYING	Assist project completion timelines with fast drying properties
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
AUSTRALIAN STANDARD	AS2311
WATER BASED FORMULA	Easy clean up with water

DATASHEET

5 YEAR GUARANTEE

Taubmans® EASYCOAT® Ceilings Paint is guaranteed to resist mould growth caused by airborne spores for 5 years if used in accordance with printed directions on pack and applied to suitable and properly prepared surfaces. If this guarantee is not met, we will replace the paint or refund your money. This guarantee is given by PPG Industries Australia Pty Limited and applies to defects in the manufacture or formulation of the paint. This guarantee does not cover mould growth from contaminated substrates or mould problems caused by environmental or underlying structural issues (e.g. localised high humidity, areas of low ventilation, structural damp or water ingress due to leaks), or paint failure caused by other factors beyond our control. We are not liable for the cost of labour or any other direct or indirect loss or damage arising from a breach of this guarantee. Customers are responsible for all costs of claiming under this guarantee. Claims must be submitted to taubmansinfo@ppg.com with a copy of purchase receipts for review and investigation. Subsequent actions will be determined upon initial investigation. The benefits provided by this guarantee are in addition to other rights and remedies under the law. If you are a consumer within the meaning of the Australian Consumer Law: Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

APAS APPROVED

APAS 0260/4

GOOD OPACITY

LOW VOC PRODUCT

VOC <5g/L

PRODUCT SPECIFICATIONS

FLAT

Designed to produce flat uniform finish with no roller marks

GLOSS LEVEL

1-2 at 60° (% at a 60 degree angle)

VOC LEVELS

<5g/Litre

DRY TIMES: TOUCH DRY

30 mins

DRY TIMES: RECOAT

2 hours

SDS

SDS available from the Taubmans Website taubmans.com.au

WHITE BASE

Tint your desired colour from a White base

SIZES AVAILABLE

1L
2L
4L
10L
15L

SURFACE PREPARATION

TEMPERATURE MIN

10 (°C)

TEMPERATURE MAX

35 (°C)

PREPARATION

Surfaces must be clean, dry and free from all contamination. Treat mould with Flood® Mould Action or bleach then rinse with clean water. Allow time for the surface to dry. Apply painter's masking tape to fittings which can't be removed, and around edges which may be difficult to paint around.

DATASHEET

PREVIOUSLY PAINTED: Remove all loose and flaking paint by scraping or sanding previously painted areas until smooth. Fill surface defects with suitable filler or sealant. Apply one coat of EASYCOAT Prep to bare or filled areas.

NEW WORK: Apply one coat of EASYCOAT Prep on paper faced plasterboard, fibre cement, masonry & timber. Use plaster sealer over set plaster.

EASYCOAT Prep is a Sealer & Undercoat in one. One coat makes it easier to paint over new work or existing paint, as it allows for good adhesion and blocks out dark and existing colours. It also provides a smoother and more professional looking topcoat.

CARE AFTER PAINTING

Avoid exposure to steam for 48 hours.

APPLICATION

WET FILM THICKNESS

60 -65 microns

DRY FILM THICKNESS

25 - 30 microns

STIRRING

Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency

NAP ROLLER

10mm - 14mm Pile Roller

CURING

Avoid exposure to steam and condensation for 48 hours after painting.

COVERAGE

Up to 16m²/litre

COATS REQUIRED

Two

BRUSH, ROLLER, SPRAY

Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.

PRECAUTIONS

GENERAL SAFETY INFORMATION

WALL PAINTS

SAFETY

Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

CEILING

SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

FIRST AID INFORMATION

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

DATASHEET

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686
Further information: www.taubmans.com.au

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au