

DATASHEET

Taubmans Armawall Trowel 2mm

TAUBMANS

Product Code:
305010


Taubmans Armawall Trowel 2mm

Taubmans Armawall Trowel On 2mm finish is a durable, high build acrylic texture finish with 2mm aggregates. Applied by trowel and finished with a polystyrene float, that gives Armawall Trowel On finish its distinctive texture patterns. Trowel is generally overcoated with Armawall Impact, Armawall Satin, Armashield or Armawall Roll On Membrane.

USES

Exterior masonry, Exterior cement render, masonry, fibrous cement sheeting, AAC panels and blocks, bricks and blockwork and most common building substrates.

FEATURES AND BENEFITS

FINISH	Trowel Finish – Attractive, contemporary, aesthetic appearance
PROVEN PERFORMANCE	Proven performance in all climates
VAPOR PERMEABILITY	Allows substrate to breathe to reduce moisture entrapment
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
WATER BASED FORMULA	Easy clean up with water

PRODUCT SPECIFICATIONS

COLOUR RANGE	Available in a wide range of colours
PROFILE	High
MATT	<p>Can be applied to uneven surfaces in order to hide imperfections.</p> <p>May mark more easily than high sheen products, so is therefore not recommended for high traffic areas.</p> <p>Ideal for interior walls; an ultra-washable, stain resistant matt finish.</p> <p>Ideal for exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel. Not suitable for surfaces used to collect drinking water</p>

DATASHEET

VOC LEVELS	< 1g/Litre
DRY TIMES: TOUCH DRY	60 mins
DRY TIMES: RECOAT	72 hours. Note: This may be lengthened in damp, cold or humid conditions. Do not apply at temperatures below 10°C.
15L AVAILABLE SIZES	15L
SDS	SDS available from the Taubmans Website taubmans.com.au
WHITE BASE	Tint your desired colour from a White base

Surface Preparation

GENERAL-ARMAWALL	Surface preparation is the responsibility of the Applicator, Builder, Renovator or Main Contractor. Armawall Surface Preparation Products are designed to perform at their optimum when used as part of an Armawall Texture Coating System.
-------------------------	---

SURFACE PREPARATION

MASONRY SURFACES	New cement render, masonry and concrete surfaces should be allowed to cure for 28 days. Off form concrete should be thoroughly cleaned by acid etching, water or sand blasting to ensure all bond breaker oils are removed. All masonry surfaces should be primed with Armawall Primer (thinned 50% with water) prior to the application of Armawall Trowel-On. Seal tilt slab concrete with Armawall Sealer/ Bonder thinned 50% with i coat LO - 2 Thinner to ensure adhesion of topcoats. Previously painted surfaces in sound condition should be scrubbed down with detergent and fresh water, fresh water washed and allowed to dry. Previously painted enamel surfaces should be undercoated with Taubmans Tradecoat. Surface irregularities such as blow holes and profile defects may require patching with Armawall Smooth Patch or Armawall Coarse Patch prior to system application.
SUBSTRATE MOISTURE CONTENT (ARMAWALL)	Moisture content of the substrate must be no greater than 15% wood-moisture-equivalent (WME) prior to or during application, to ensure optimal coating system performance
PREVIOUSLY PAINTED	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)

APPLICATION

ODOUR	Low
APPLICATION	This product is applied with a steel trowel and scratched off vertically (or using a circular motion "swirl") with a polystyrene float to produce the texture finish
WET FILM THICKNESS	Variable

DATASHEET

DRY FILM THICKNESS	2mm (Variable)
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
NAP ROLLER	Steel Trowel
STAINLESS STEEL TROWEL POLYSTYRENE FLOAT	Working in an upward action with the trowel, hold trowel & material against wall and evenly apply material. Now working across the wall, in a horizontal action continue to spread the material evenly. This will also help even out trowel shudder marks. Once you start to see the tips of the aggregate correct depth has been reached. To create the Vertical style of finish, take the polystyrene float and pass lightly over the texture in a VERTICAL ACTION working top to bottom in short sharp passes. To create the circular style of finish, take the polystyrene float and pass lightly over the texture in a CIRCULAR ACTION working left to right in small circle passes.
STAINLESS STEEL TROWEL, RED PLASTIC FLOAT	Working in an upward action with the trowel, hold trowel & material against wall and evenly apply material. Now working in a tight circular motion with the RED PLASTIC FLOAT, Run the float over the surface, remember to keep the float FLAT on the wall to ensure even & smooth back the texture. Remember that the RED PLASTIC FLOAT will act as a razor and shave off any high areas of material. This can lead to some material wastage if the material is applied to thickly.
COVERAGE	0.6 m ² /litre
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
COATS REQUIRED	One or Two

PRECAUTIONS

GENERAL SAFETY INFORMATION	<p>WALL PAINTS</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p> <p>CEILING</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
FIRST AID INFORMATION	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au</p>
ENVIRONMENT INFORMATION	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DATASHEET

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au