

DATASHEET

Taubmans Wood Primer

TAUBMANS

Product Code:
111537



Taubmans Wood Primer

Taubmans Wood Primer is a high-performance prepcoat specifically formulated to seal and protect exterior timber from mould and mildew. The oil-based formula is highly recommended for tannin rich timbers such as Jarrah, Merbau, etc where tannin blocking is required, and also provides adhesion for the paint system. The foundation for a superior finish.

USES

Ideal for new and weathered bare timber, and previously painted timber.

FEATURES AND BENEFITS

AUSTRALIAN MADE	Our Aussie Heritage: Since our creation over a century ago in 1897 by George Henry Taubman, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success with our state-of-the-art plant in Clayton, VIC.
MOULD RESISTANT	Helps prevent the growth of mould, mildew and fungus in damp areas
HIGH OPACITY	Excellent hiding properties.
EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
AUSTRALIAN STANDARD	AS2311, AS3730.13
APAS APPROVED	APAS 0018/1

PRODUCT SPECIFICATIONS

4L AVAILABLE SIZES	4L
10L AVAILABLE SIZES	10L
SDS	SDS available at www.ppgmsds.com.au
DRY TIMES: TOUCH DRY	4 hours

DATASHEET

DRY TIMES: RECOAT 16 hours

SURFACE PREPARATION

TEMPERATURE MIN 10 (°C)

TEMPERATURE MAX 35 (°C)

RECOATHUMIDITYPERCENTAGE 50 (%)

NEW/BAREWORK All surfaces must be clean and dry with all defects sanded smooth.

APPLICATION

WET FILM THICKNESS 80 - 85 micron

DRY FILM THICKNESS 25 - 30 micron

COVERAGE Up to 12 m2/litre

COATS REQUIRED One

STIRRING Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency

BRUSH, ROLLER, SPRAY Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.

PRECAUTIONS

DANGER FLAMMABLE LIQUID AND VAPOUR Warning. Flammable hydrocarbon liquid. Keep out of reach of children. Keep lid on when not in use. Wear solvent resistant gloves and eye protection when using. Ensure adequate ventilation and do not breathe vapour.

GENERAL SAFETY INFORMATION WALL PAINTS
SAFETY
Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

CEILING

SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

DATASHEET

FIRST AID INFORMATION

IF SWALLOWED – Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT – Flush with plenty of water. Always seek medical advice.

SKIN CONTACT – Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION – Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA – 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686
Further information: www.taubmans.com.au

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au